

EXIT DEVICES

EXIT CONTROL LOCK

BENEFITS—

- Attack resistant design withstands over 2200 lbs. of outside pull force.
- Proven durability and reliability at a reasonable price.
- Reduces employee and customer theft.
- Easy to install.
- Time tested construction resists attack from the inside.
- Easy to see if lights go out.
- Meets UL Listed Panic Hardware 988N-Grade 3
- 10-year limited warranty.

The ECL-230D is a code compliant, battery operated, rugged dead bolt panic device with steel plate and photo-luminescent sign providing managed security and a 100 decibel alarm for secondary exits.

FEATURES—When armed, pressing the exit bar retracts the deadbolt and sounds the alarm to allow exit. Locking and unlocking the dead bolt always arms and disarms the alarm. Resetting the alarm can only be accomplished with a control key. 100 decibel alarm powered by one standard 9 volt battery (included). 1" throw, saw resistant deadbolt. Rugged housing with key lock. Corrosion resistant alloy lock body. Non handed.

FOR NARROW STILE DOOR ORDER THE BACK PLATE KIT DET-ECL475K. (shown below)



Meets ADA Requirements



Rim Cylinder Not Included.
(sold separately)

Stock No. **Description**
DET-ECL230D Exit Control Unit


SPECIFICATIONS

- SIZE:** 10-3/8" H x 5-3/4" W x 3-3/4" D (lock case)
3-1/8" H x 12-7/8" W (push plate and bar)
- PADDLE:** 3" H x 8-7/8" L. Florescent orange.
- DOOR THICK.:** 1-3/4" to 2-1/4". Minimum door with of 20".
- DOOR STILE:** Minimum 5-3/4" with ECL-437K strike.
For narrow stile door order optional kit
DET-ECL-475K. Fits max. stile of 1-7/8"
- BACKSET:** For door preparation of 2-3/4"
- CYLINDER:** Accepts 5-pin though 7-pin standard and I/C rim cylinders (not included). Sold seperately.
- STRIKES:** 1ea ECL437K Adjustable Surface (standard)
1ea ECL439K Mortise Strike Plate Kit.
- FINISH:** Die-cast aluminum alloy housing with Corvel Detex Silverado finish. Florescent orange paddle.

MISCELLANEOUS



DET-ECL475K
Decorative Back
Plate Kit for use on
narrow stile doors.



DET-ECL435K
Adjustable surface keeper. "L" & "Z"
bracket for double door applications.



DET-PP5572-15
Replacement Cover Lock.

**REMEMBER: If you don't see what you need,
please contact us with your requirements.**

EXIT DEVICES

EAX-500 SERIES EXIT

BENEFITS—

- Low-cost, self-contained door alarm with piezo horn that sounds to warn unauthorized use of a door or gate.
- Secure, tamper resistant housing.
- Quick, easy installation saves time and money.
- 3-year limited warranty.

The EAX-500 Series is designed for applications requiring an alarmed exit device on secured doors. The alarm, with approximately 100dB, will sound when an unauthorized exit occurs. The EAX-500 with its redesigned shape and smaller size make it the ideal choice for quick and easy installations on emergency exit and restricted doors.

FEATURES—Patented plastic template allows for foolproof alignment of internal magnetic door contact and accurate installation. Tapered cover allows for installation on narrow stile doors, 2" minimum. Intelligent circuit sensed the external magnet location automatically and sets the correct door handing. Patented cam assembly automatically adjusts for different sizes of cylinders without use of spacers. Alarm can only be silenced proper control key. Extended bypass (now a standard feature) allows alarm to remain bypassed when door is open and automatically rearm upon door closing. Modern graphics on cover to demonstrate key rotation and operation. 100dB piezo alarm. 9VDC battery operated with low battery alert. LED visual and audible arming indicators. Field selectable 2-minute auto rearm, if desired. Field selectable status indicators, if desired.



Mortise Cylinder
not included - order
seperately

DETEX[®]
Life Safety and Security Door Hardware

Stock No. Description
DET-EAX-500 Surface Door Mount

PHYSICAL SPECIFICATIONS:

Dimensions: 2.10"W x 2.375"D x 7.70"L

Housing: Grey finish polymer case

Battery: 9V Energizer battery included

Warning Sign: 1 ea red and white pressure sensitive sign reading "EMERGENCY EXIT ONLY ALARM WILL SOUND". (11" x 3-3/8")

Cylinder: (not included)

Alarm accepts 5, 6, and 7 pin standard and interchangeable core mortise cylinders with a standard Yale cam for inside control. Rim cylinder required for outside control.

We can do the keying for you...



KEYING ALIKE
MASTER KEYING
GRAND MASTER KEYING
PROTECTO KEYING
CONSTRUCTION KEYING
and INTERCHANGEABLE CORES

Do your own keying? We can help there too!
Check pages 387-401 for keying kits and keying accessories.