

# ELECTRIC STRIKES

## 1006 SERIES STRIKES

The 1006 Series meets or exceeds every standard developed for electric strikes. With 27 faceplate options (some are special order), the 1006 can accommodate virtually every type of lockset on the market. The 1006 features an innovative dual interlocking plunger design and heavy-duty, all stainless steel construction. Factory tested to exceed 3,000 lbs. of static strength and 2,000,000 cycles of operation; the 1006 is in a class of its own.

# hes

HES-1006U With  
HES-J (Shown)



**Stock No. (Body only)**  
**HES-1006U-12/24DC-BLK**  
**FINISH: BLK** Nylon Black Coated

**TO ORDER, SPECIFY:**  
Strike No. (HES-1006U-12/24DC BLK)  
Faceplate No. (HES-J OPTION)  
• See below for Faceplates

### SPECIFICATIONS:

- UL 10C, 3 hour fired rated (fail secure only)
- UL 1034, burglary resistance
- ANSI/BHMA 156.31 - 2001, **Grade 1**
- NFPA specification 252
- ASTM specification E 152
- MEA 166-00-E
- ANSI A250.13-2003, ASTM E1886-97, ASTM E330-98, windstorm resistant
- Patent #4,017,100, #4,026,589, #4,595,220.

### ELECTRICAL:

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC

### STANDARD FEATURES:

- Tamper resistant — heavy duty construction
- Model 1006 — Fail secure
- Fail secure — unlocked when energized
- 3000 lbs static strength
- Tested at 2,000,000 cycles of operation
- Internally mounted solenoid
- Non-handed
- Dual voltage — field selectable, 12 or 24VDC
- All stainless steel construction for corrosion resistance, strength, and durability
- Horizontal Adjustment
- 1000-15 — Trim enhancer (goof plate)

### FINISHES:

- **630** Satin Stainless Steel

### WARRANTY:


- 5-year limited warranty

### ACCESSORIES:

**HES-2001M** Plug-in bridge rectifier. Converts AC to DC. .35 V, 1 Amp

**HES-2006M** Plug-in Buzzer - Audible operation indication.

square corners &  
flat faceplate



### FACEPLATES—(Other faceplates by special order)

#### **HES-J 630** (Satin Stainless Steel Finish)

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Cylindrical locksets up to 3/4" throw and all locksets with center-lined bolts.



#### **HES-K 630** (Satin Stainless Steel Finish)

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.


**For use with:** Mortise locks with a deadlatch positioned **above** the latchbolt. Compatible locksets: Accurate, Arrow, Baldwin, Marks, PDQ.



#### **HES-KD 630** (Satin Stainless Steel Finish)

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Mortise locks with a deadlatch positioned **above** the latchbolt. Compatible locksets: Jackson, Sargent (7700 & 8100 series), Schlage, Yale



#### **HES-AM 630** (Satin Stainless Steel Finish)

**Operation:** Latchbolt and deadbolt are released by a single keeper. The keeper is held open to recapture the latchbolt and the deadbolt when the door is closed.

**For use with:** Mortise locks with normally extended 1" deadbolt and a deadlatch positioned **below** the latchbolt. Compatible locksets: Corbin/Ruswin, Falcon, Sargent (7800, 8200 & 9200 series)

**Don't see the HES strike  
you need?? Call us.**

# ELECTRIC STRIKES

## 5000 SERIES STRIKES

The patented 5000 series is a compact, heavy duty, and high performance electric strike designed for low profile openings where there is limited space behind the jamb. This includes narrow style aluminum jambs and jambs with protruding glass inside. The 5000 series has a static strength of 2400 lbs. The field selectable fail secure/fail safe unit is easy to install and accommodates 1/2" latchbolts.



**Stock No. (Body Only)**  
**HES-5000-12/24DC** 12/24VDC

**TO ORDER, SPECIFY:**  
 Strike No. (HES-5000-24D)  
 Faceplate No. (HES-501A OPTION 630)  
 • See below for Faceplates

### SPECIFICATIONS:

- ANSI/BHMA 156.31 - 2001, **Grade 1**
- UL 1034, burglary resistance rated
- ASTM specification E 152
- NFPA specification 252
- MEA 166-002
- Patent #5,934,720

### ELECTRICAL:

- .22 Amps @ 12VDC
- .11 Amps @ 24VDC

### STANDARD FEATURES:


- Tamper resistant — heavy duty construction
- 2400 lbs static strength
- Tested at 500,000 cycles of operation
- Field selectable fail secure/fail safe operation
- Internally mounted solenoid
- Non-handed

### FINISHES:

- **613** Bronze toned
- **630** Satin Stainless Steel

### WARRANTY:

- 5-year limited warranty



HES-2001M



HES-2006M

### ACCESSORIES:

**HES-2001M** Plug-in bridge rectifier. Converts AC to DC. .35 V, 1 Amp

**HES-2006PM** Plug-in Buzzer - Audible operation indication.

### FACEPLATES—(Other faceplate by special order)

#### HES-501 OPTION 630

**Operation:** After release, the keeper returns to the locked position.

**For use with:** Cylindrical locksets in ANSI metal jambs. For use with latchbolts up to 1/2" throw.

#### HES-501A OPTION 630

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Cylindrical locksets. For use with latchbolts up to 1/2" throw. Includes universal mounting tabs. Aluminum frames.

#### HES-501B OPTION 613 or 628

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Cylindrical locksets. For use with latchbolts up to 1/2" throw. Includes universal mounting tabs. Aluminum doors and frames with radiused front.

#### HES-503 OPTION 613 or 630

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Cylindrical locksets. For use with latchbolts up to 1/2" throw. Includes universal mounting tabs.

#### HES-504 OPTION 630

**Operation:** After releasing the latchbolt, the keeper returns to the locked position.

**For use with:** Cylindrical locksets. For use with latchbolts up to 1/2" throw. Four point mounting for wood installations.

square corners & flat faceplate



square corners & flat faceplate



square corners & flat faceplate



square corners & flat faceplate



square corners & flat faceplate



# ELECTRIC STRIKES

## 7000 SERIES STRIKES

The 7000 series has a modular design to accommodate both cylindrical and rim exit locksets. The 7000 series will accommodate various types of latchbolt from 5/8" to 3/4" throw. The unique design of the keeper module allows the unit to operate under excessive door loading (approximately 30 lbs.) The 7000 series has an internally mounted solenoid for ease of installation in metal, aluminum and wood jambs. The heavy duty construction of the 7000 series electric strikes makes them ideal for high usage applications.



HES-7000U With HES-701 (Shown)



**Stock No. (Body Only)**

**HES-7000U-12DC** 12VDC

**HES-7000U-24DC** 24VDC

**TO ORDER, SPECIFY:**

Strike No. (HES-7000U-24DC)

Faceplate No. (HES-701 OPTION 630)

• See below for Faceplates

**SPECIFICATIONS:**

- ANSI/BHMA 156.31, **Grade 2**
- UL 1034, burglary resistance rated
- ASTM specification E 152
- NFPA specification 252
- MEA 166-000-E
- Patent #5,484,180

**ELECTRICAL:**

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC

**STANDARD FEATURES:**


- Tamper resistant — heavy duty construction
- Strike depth — 1-11/16"
- 30 lbs. of door resistance (fail secure)
- Field selectable operation fail secure/fail safe
- Internally mounted solenoid
- Non-handed

**FINISHES:**

- **628C (630)** Silver Nylon
- **630** Satin Stainless Steel

**WARRANTY:**

- 3-year limited warranty



HES-2001M



HES-2006M

**ACCESSORIES:**

**HES-2001M** Plug-in bridge rectifier. Converts AC to DC. .35 V, 1 Amp

**HES-2006M** Plug-in Buzzer - Audible operation indication.



**FACEPLATES—**(Other faceplate by special order)

**HES-790 OPTION 630**

**Operation:** After releasing latchbolt the keeper returns to the locked position.


**For use with:** Cylindrical locksets up to 5/8" throw.



**HES-792 OPTION 630**

**Operation:** After releasing latchbolt the keeper returns to the locked position.


**For use with:** Cylindrical locksets up to 5/8" throw.



**HES-786 OPTION 628C**

**Operation:** After releasing pullman latch, the keeper returns to the locked position.

**For use with:** Rim exit devices in aluminum jambs and surface mounted vertical rod exit devices with up to 3/4" pullman latch. Compatible Locksets: Adams Rite, American Device, Arrow, Doramatic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale.



**HES-789 OPTION 628C**

**Operation:** After releasing pullman latch, the keeper returns to the locked position.

**For use with:** Rim exit devices in aluminum jambs with up to 3/4" pullman latch. Compatible Locksets: Adams Rite, American Device, Arrow, Doramatic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale.

# ELECTRIC STRIKES

## 9600 SERIES STRIKES

Completely surface-mounted, the 9600 Genesis™ is the first of its kind. The 9600 accommodates rim exit devices in metal or wood jambs. The 9600 features an internally mounted solenoid and two stainless steel, independently operating locking mechanisms. The 9600 is easy to install, with all components of the 9600 encased in the 9" x 1-3/4" x 3/4" faceplate, requiring no cuts to the jamb prior to installation.

### SPECIFICATIONS:

- ANSI/BHMA 156.31, **Grade 1**
- ASTM E 152
- NFPA 252
- Patent #6,390,520

### ELECTRICAL:

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC

### STANDARD FEATURES:

- Static strength: 1,500 lbs
- Endurance: 1,000,000 cycles
- 12 or 24 VDC field selectable
- Tamper resistant — heavy duty construction
- Completely surface mounted
- Field selectable operation fail secure/fail safe
- Internally mounted solenoid
- Non-handed
- Horizontal lockdown screws
- Accommodates up to 3/4" throw pullman latch

### FINISHES:


- **630** Satin Stainless Steel

### WARRANTY:

- 5-year limited warranty

hes

Stock No.  
**HES-9600-630** 12/24VDC



HES-2001M

### ACCESSORIES:

**HES-2001M** Plug-in bridge rectifier. Converts AC to DC. .35 V, 1 Amp



HES-2006M

**HES-2006M** Plug-in Buzzer - Audible operation indication.

**REMEMBER: If you don't see what you need,  
please contact us with your requirements.**