## **CAM LOCKS**



## SMALL PIN - NATIONAL KEYWAY

**GENERAL FEATURES**—

Rekeyable: Easily rekeyable via cylinder retainer clip

Body: Zinc die cast lock body

Cylinder: Zinc die cast pin tumbler cylinder

Functions: Non-key retaining (standard). Alternate key-


retaining shifters are available separately. **Cams:** 2 reversible cams work in all positions

Face: 1" face covers splintering, no additional trim ring

required

Finish: 26D. Other finishes by special order.

KEYING INFORMATION— Keyway: National D4291 (4 pin) Stock keying: KD/KA - 4 pin standard Stock KA#: 915. Other KA# by special order.



Stock No.
OS-DCN1-26D KD
OS-DCN1-26D KA915
OS-DCN2-26D KD
OS-DCN2-26D KA915
OS-DCN4-26D KD
OS-DCN4-26D KD

_						Cylinder
		Thickness	Cam(X)	Cam(Y)	Cam(Z)	Length(A)
	OS-DCN1	3/4"	1-1/16"	3/4"	1-3/8"	1"
	OS-DCN2	7/8"	1-3/16"	7/8"	1-1/2"	1-1/8"
	OS-DCN4	1-1/2"	1-13/16"	1-1/2"	2-1/8"	1-3/4"

## IC CORE - SMALL FORMAT

**GENERAL FEATURES-**

Certifications: Passed ANSI/BHMA A156.11 Grade 1

performance requirements **Cylinder diameter:** 1-1/8"

Hole Size: 1-5/32"; Across flats: 7/8" Max. material thickness: 1-1/8" Min. material thickness: 0.08" Retrofits: Best 1E7D4 or 1E7E4

Functions: Includes all parts for key-retaining or non-

key-retaining function **Body:** Zinc die cast body


Finish: 26D. Other finishes by special order.

**KEYING INFORMATION—** 

Cores: Not included. Order seperately.

**Accepts:** Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores







-I 9/32" <del>→</del>



Stock No. OS-720LM/DM-26D

Less cores, see below for





## **SMALL FORMAT CORES**

Stock No. Length AR-100CR-UC 6 pin AR-7100CR-UC 7 pin

**ARROW™** 

Keyways: 1D, AB, BB, DB, EB, FB, GB, HB, JB, KB, MB.

Finishes: 4-Satin Brass, 26D-Satin Chrome

To Order, Specify:

Stock No. Keyway and Finish (AR-C6S-UC AB 26D)

\*ZIPE LOCK COMPANY